




Walk In Coolers and Freezers by







MODEL: BL86-C


COOLER 35°

REFRIGERATION UNIT

## -7'-10" [94"]-.88 **ELEVATION**

SHOWN W/ RIGHT HINGE

(LEFT HINGE AVAILABLE)



PRODUCT SPECIFICATI	ONS	ŀ
MODEL:	BL86-C	
INTERIOR/EXTERIOR FINISH	MILL EMB. ACRYLUME	
COMPT ELECTRICAL (VOLTS/Hz/PH)	115/60/1	
COMPT AMP.	0.8 Amp	
REFRIG. SYSTEM ELECT (VOLTS/Hz/PH)	208-230/60/1	
REFRIG. SYSTEM AMP.	4.7 Amp	
CORD + NEMA 6-15R PLUG		
REFRIG. SYSTEM WEIGHT.	195 Lbs	
TOTAL SHIP WGHT APPROX. (2 PALLETS)	805 Lbs	
TOTAL SHIP CUBIC FEET APPROX.	201 CuFt	



GENERAL NOTE

GENERAL NOTE

NOTICE TO GENERAL CONTRACTOR

AND SUB-CONTRACTOR, UNIT

QUARRY TILE OR CONCRETE

WEARING FLOORS, THE MEDITALE

FACINES MAY BE SUB-CESSIVE

THORN SHAY BE SUB-CESSIVE

THE SUB-CESSIVE

THORN SHAY BE SUB-CESSIVE

THE SUB-CESSIVE

THORN SHAY BE SUB-CESSIVE

THE SUB-CESSIVE

THE SUB-CESSIVE

THE SUB-CESSIVE INCIDE TUMES ON ALUMINUM AND STANLESS STELL IN ADDITION, METAL SURFACES MUST BE PROTECTED FROM LIME AND OTHER CHEMICALS FOUND IN CONCRETE BY—PRODUCTS.
PETROLEUM BASED PROTECTION MUST BE APPLIED BETWEEN CONCRETE AND THE METAL SURFACES. LIQUID TAR, BRUSHED OR SPRAYED ABOVE THE CONCRET CONTACT LINE, HEAVY EPOXY PAINT, 8 MIL POLYETHLYLENE H.D. BLACK DOUBLE LAYERED, 30 LB. ASPHALT

CONSTRUCTION N S F CONSTRUCTION Project Name:

ARCTIC INDUSTRIES, INC.

P.0#:

APPLICATION: MODEL: BL86-C

NOTES:

FLOOR MUST BE LEVEL SMOOTH AND CLEAR OF OBSTRUCTIONS TO ACCEPT WALK-IN PANELS. ALSO, THERE MUST BE A MINIMUM OF 2"
CLEARANCE AROUND ALL SIDES OF
THE WALK-IN UNIT PROPER
CIRCULATION.

VERIFY ALL DIMENSIONS AND SPECIFICATIONS BEUNITE APPROVING DRAWINGS

IPORTANT: ALLOW 2 FEET LEARANCE ABOVE UNIT TO REMOVE OP PANEL AND TO ALLOW SERVICE

TTRUCTURE MUST BE NOT MASKED TO BUILDING CEILING, BLOCKING AIR LOW TO UNIT.

SIGNED APPROVED PRINT

MUST BE REC'D. B/4 FAB. ☐ APPROVED AS DRAWN

Checked By: Drawn Bv: R.PUPO ARCTIC CREATED: Scale: NOT TO SCALE 2014

DRW No:

BL86-C